科 THE BOLD LOOK
勒 OF KOHLER®
全 球 厨 卫 经 典

欧芙 OVE
安装说明书
INSTALLATION INSTRUCTIONS
压克力按摩浴缸
ACRYLIC WHIRLPOOL
K-1709T K-1709T-H

BEFORE YOU BEGIN

- Please read these instructions carefully to familiarize yourself with the required tools, materials, and installation sequences. Follow the sections that pertain to your particular installation. This will help you avoid costly mistakes. In addition to proper installation, read all operating and safety instructions.
- All information is based on the latest product information available at the time of publication. Kohler China Ltd. reserves the right to make changes in product characteristics, packaging, or availability at any time without notice.
- These instructions contain important care, cleaning, and warranty information-**please leave these instructions for the consumer.**

安装之前

- 请仔细阅读此说明书以熟悉所需要的工具、材料及安装顺序。遵循适合您的特定安装要求的各项内容，避免昂贵的损失。除了要正确安装外，还应阅读操作及安全说明。
- 所有的资料是按最新出版的产品资料编写而成。科勒中国有限公司保留任何时候无须通知即可改变产品特性、包装或产品可供类型的权利。
- 说明书包括重要的安装、清洁及保养方面的内容，请把这些资料交给用户阅读。

ROUGHING-IN & DIMENSIONS

安装尺寸说明及尺寸图

A. Ordering Information

Hardware:		
Drain	17295T-CP	Optional

A. 订购信息

配件：		
排水	17295T-CP	推荐使用

B. Required Electrical Service

Dedicated branch circuit required, protected with Class A Ground-Fault Circuit-Interrupt (GFCI):	
Pump	220~240V，5.1A，50Hz，750W.
Heater HC103P	220~240V，4.5A，50Hz，1000W.

B. 所需的电源线路

需要专用的分支电路，并以A级接地事故断路器(GFCI)保护：	
水泵	220~240伏特，5.1安培，50赫兹。750瓦。
加热器HC103P	220~240伏特，4.5安培，50赫兹，1000瓦。

上海科勒有限公司
上海市浦东星火开发区民乐路368号 邮编：201419

ⓒ版权为科勒中国有限公司所有，2006
ⓒCopyright Kohler China Ltd., 2006

C. Product Information

C. 产品资料

K-1709T, K-1709T-H

Fixture*	Basin area	Top area	Weight
Bathing well	1092×427mm	1585×625mm	42kg
	Water depth	Capacity	
To overflow	327mm	214L	
* Approximate measurements for comparison only.			

Pump	HP	Voltage	Frequency	Amperage
1-Speed	1 HP	220~240 V	50 Hz	5.1A
Heater	HP	Voltage	Frequency	Amperage
HC103P	1.36HP	220~240 V	50~60 Hz	4.5A

浴缸	底部	顶边	重量
面积	1092×427毫米	1585×625毫米	42公斤
	深度	容积	
到溢水口	327毫米	214升	
*为比较浴缸所用的参考数值。			

水泵：	马力	电压	频率	电流
单速	1匹	220~240 伏	50 赫兹	5.1安培
加热器	马力	电压	频率	电流
HC103P	1.36匹	220~240 伏	50~60赫兹	4.5安培

D. Installation

D. 安装须知

Read the entire installation instruction before beginning the installation.

开始安装之前，请先阅读整份说明书。

E. Dimensions

E. 尺寸图

Roughing-In Notes		
Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.		
No change in measurements if connected with drain illustrated.		
Access panel		
Pump/Control	500W×400H mm	Required

安装尺寸说明		
所有尺寸为公称尺寸。		
如果采用图示排水配件，数值将保持一致。		
最小检修门		
水泵/控制	500宽×400高 毫米	必须设置

Unit: mm
单位: 毫米

K-1709T, K-1709T-H



PRODUCT NOTICES

A. Installation Hazard Notification

DANGER: Risk of fire, electric shock, or injury to Persons. Read important safety instructions on inside front cover of these instructions.
WARNING: Risk of electrical shock. A licensed electrician should make all electrical connections.
WARNING: Risk of electrical shock. Connect only to a circuit protected by a Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB).
WARNING: Risk of electrical shock. Disconnect power before servicing.
WARNING: Risk of injury or property damage. Please read all instructions thoroughly before beginning installation, including the following Product Requirements.
NOTICE: Follow all local plumbing and electrical codes.

B. Factory-Assembled Features

Factory installed components include pump and air switch transmitter. No installation is needed.
The whirlpool pump and piping are factory assembled.

WARNING: Unauthorized modification may cause unsafe operation and poor performance of the whirlpool. Do not relocate the whirlpool pump, or make other modifications to the whirlpool system, as this could adversely affect the performance and safe operation of the whirlpool. Kohler China shall not be liable under its warranty or otherwise for personal injury or damage caused by any such unauthorized

产品注意事项

A. 安装危险警告

危险：有起火、触电或人员受伤的危险。请阅读本说明书封面内页的重要安全指示。

警告：有触电的危险。请找合格的电工来进行所有的线路连接。
警告：有触电的危险。仅能和由接地故障断路器(GFCI)保护的电路相接。

警告：有触电的危险。工作之前先切断电源。

警告：有受伤或财物受损的危险。开始安装之前，请先彻底阅读所有说明，包括以下的产品要求。

注意：请遵守所有的本地卫生管道和电气规范。

B. 由厂家组装的部件

由厂家安装的机件包括水泵和空气开关传输器，不须自行安装。
按摩浴缸的水泵和水管都已经在工厂组装好。

警告：如果未经过授权而自行改装，可能造成按摩浴缸在操作上不安全及性能不良。请勿将按摩浴缸的水泵移位或对按摩浴缸系统做任何改装，否则可能对按摩浴缸的性能和安全操作造成严重影响。若由于未经过授权而自行改装造成人员受伤或损害，科勒中国有限公司将不依据担保条例予以负责。

PRODUCT REQUIREMENTS

A. Summary Of Key Requirements

- Observe all local plumbing codes.
- Install the unit to a level subfloor.
- Provide properly-dimensioned framing.
- Baths are designed for a variety of installations, depending upon the model chosen.

K-1709T
Drop In installation is recommended.

产品要求

A. 关键要求的总结

- 请遵守当地的卫生管道施工规范。
- 在水平的未装修的底层地板上安装浴缸。
- 提供适当尺寸的结构。
- 按摩浴缸的设计适用于不同的安装方式，请按型号来选定。

K-1709T
建议嵌入安装。

B. Plumbing Specifications

If using a rim-mounted bath faucet, flexible connections between the valves and spout may be required. Confirm adequate mounting, connection space of specified faucet for your installation.

Confirm adequate support for the faucet; large faucets that may inadvertently used as a means of support are not appropriate or safe or this installation.

B. 卫生管道规格

如果是在边缘安装水龙头，必须以软管连接阀体和水龙头，确认安装是否适当，及指定的水龙头连接空间是否足够。

确认水龙头的支撑是否稳固；大型的水龙头可能会被误用为支撑之用，而使安装不适当或不安全。

C. Product Inspection

Carefully unpack and inspect the whirlpool for damage. Leave all materials in the carton during constructions to prevent damage.

NOTICE: Make sure both union connections to the pump are securely tightened.

C. 产品检查

小心打开包装箱并检查按摩浴缸是否损坏，施工期间将所有的材料都留在箱内，以防止损坏。

注意：确定水泵的两个联合接头已经固定上紧。

D. Electrical Connection

1. Pump
   The installation must have a 30mA Earth Leakage Circuit Breaker. The GFCI protects against Line-to-Ground shock hazard. Use a 220-240V, 10A (minimum), 50Hz dedicated service for the whirlpool.
2. Heater
   1) Should be protected by a ground fault circuit interrupter (GFCI), The GFCI protects against Line-to-Ground shock hazard. Use a 220-240V, 10A(minimum), 50Hz dedicated service for the whirlpool.
   2) Check the heater label to make sure the rated voltage is the same to yours.
   3) The earth cable uses AWG8 copper leads, and the heater supplied earth terminal.

D. 电气要求

1. 水泵
   水泵的供电线路上必须安装额定触发电流为30mA的漏电保护开关（GFCI）。漏电保护开关可避免线路对地的触电危险，请提供一条220-240伏/50赫兹，最小额定电流为10安培的专用线路供水泵使用。
2. 加热器
   1)加热器的供电线路上必须安装额定触发电流为30mA的漏电保护开关（GFCI）。漏电保护开关可避免线路对地的触电危险，请提供一条220-240伏/50赫兹，最小额定电流为10安培的专用线路供加热器使用。
   2)在电源接线前，要确认加热器铭牌上的额定工作电压与你使用的电源电压一致。
   3)地线采用AWG8铜导线，加热器提供接地线端子。

E. Clearance Requirements

Check the roughing-in and room dimensions to provide adequate available space for the bath unit.

NOTES: For applicable whirlpool models, if the optional removable apron is used, the whirlpool must be raised so the whirlpool support feet are level with the finished floor.

E. 预留尺寸

检查安装尺寸和浴室尺寸，确保有充分的空间安装浴缸。

注意：对于某些型式的按摩浴缸，如果选用可拆卸的裙边，必须将按摩浴缸抬高，以便让浴缸的支撑脚与地面同高。

F. New or Replacement Installation Requirements

This whirlpool can be installed in new or existing bathrooms.

For new installations: Position the plumbing according to roughing-in dimensions beginning on page 2. Cap the supplies, and check for leaks.
For replacement installations: Remove the old bath. Remove the old wall material (e.g. Ceramic or marble tiles) and remove any old floor covering from the area. Remove any old plumbing that does not conform to roughing-in requirements.

F. 安装新浴缸或替换旧浴缸要求

无论新的和旧的浴室，本产品均适合安装。

安装新浴缸：根据第2页开始的安装尺寸图铺设管道。堵塞供水管，并检查渗漏。

替换旧浴缸：搬去旧浴缸，清除旧墙材料(如瓷砖或大理石)，并拆除任何旧的地板贴面，拆除任何不配新浴缸尺寸的旧管道。

INSTALLATION REQUIREMENTS 安装要求

A. Tools Required B. Materials Required

- Adjustable pipe wrench
- Rule
- Level
- Safety shoes
- Safety glasses
- Square
- Screwdriver
- Pliers
- Utility knife
- Plumbers putty
- Wall coverings, as necessary
- Silicone sealant
- Gypsum cement (optional)
- Construction adhesive (optional)
- Protective covering for bathtub
- Nails

A. 所需工具

- 管道扳手
- 刻度尺
- 水平仪
- 安全鞋
- 安全眼镜
- 直角尺
- 螺丝刀
- 钳子
- 多用工具刀

B. 所需材料

- 管道用油灰
- 墙面保护罩(如需要)
- 密封硅胶
- 石灰水泥(选用)
- 建筑粘胶(选用)
- 浴缸保护套
- 钉子

SITE REQUIREMENTS 场所要求

A. 拆除旧浴缸

在存水弯处拆下排水管。清除所有旧墙材料。在旧浴缸下面塞入护板以保护地面，并如图所示把旧浴缸从安装空间拉出。

A. Old Bath Removal (If Applicable)

Disconnect the drain at the trap. Remove the old wall material. Slip boards under the old bath feet to protect the floor, and slide the old bath out of the recess as illustrated.



B. Subfloor Preparation

Check the floor under the whirlpool, and make repairs as needed. Make sure the subfloor is level.

B. 底层地板的准备

检查按摩浴缸下的地板，若需要请进行修补。请确保底层地板水平。

C. Whirlpool Area Construction Preparation

Make sure you allow for access to the pump in the event the unit requires service. When constructing the framing, allow for the thickness of sub and finish wall material (e.g. mortar mix and ceramic or marble tilling).

Drop In Installation： Refer to rough-in notes on page 2 for cut-out details. Make sure the whirlpool is supported by the supporting feet on the bottom of the whirlpool. Do not hang the bath by the rim.

嵌入安装：有关切割图样的细节请参阅第2页的安装尺寸说明。务必使按摩浴缸底部的支撑脚支撑。
不要使浴缸靠边缘悬挂。

C. 按摩浴缸支撑结构的准备

确保为水泵预留空间，以便于维修。建立结构时，请预留底层地板和完工墙壁材料的厚度(例如水泥沙浆和瓷砖或大理石)。



BEFORE INSTALLING WHIRLPOOL

安装按摩浴缸之前

A. Your new whirlpool has been manufactured to the highest possible standards, it has been factory tested and approved.

A. 本按摩浴缸质量上乘，已经工厂检测通过。

B. When removing bath from protective carton **DO NOT LIFT BATH BY PIPE WORK**. Inspect for any possible damage that may have occurred in transit.

B. 从起保护作用的纸箱中取出时，**请不要拎着管道部分将浴缸取出**。检查可能有搬运造成的损伤。

C. Identify motor access location before proceeding with installation.
NOTE：NO MOTOR ACCESS NO WARRANTY SERVICE. Ventilation must be provided in order to allow heat from motor to dissipate.

C. 安装前，请找到马达检修门的位置。
注意：无马达维修口，不能获得保修。应通风良好，保证马达散热。
请根据你的实际情况预留检修门。



PROVIDE MOTOR ACCESS AS SHOWN.
如图所示马达检修门位置。

D. IMPORTANT: Bath must be installed level on all top edges.

D. **注意**：浴缸必须水平地放置。



E. Partially Install Whirlpool Bath Drain

Install the drain on the whirlpool bath according to the drain manufacturer's instructions. When installing the drain overflow tube and hood, be sure to adequately seal along the edges of the hood to prevent leakage.

Unpack drain (17295T-CP) and ensure that the Control Cable (9b) is not twisted or awkwardly bent.
Please ensure that the bath is placed on woonden blocks or bricks to protect the waste body under the bath.

Installation steps:
1) Fit Drain Gasket Thin ⑤ to Strainer ④
2) Insert Strainer ④ into hole in bath from upper side.
3) Fit Drain Gasket Thick ⑥ to Drain Body Assy and Drain Body Assy ⑨ to underside of bath.
4) Strainer ④ to Drain Body Assy ⑨ by means of Fix Screw Strainer ③ **Do not tighten firmly at this stage**.
5) Apply a bead of silicone around the overflow hole, on the outside of the bath. Smear with silicone the inside wall of overflow hole.
6) Fit 2nd. Gasket Overflow⑭ to Over Flow Body⑨ and offer this assembly to back of overflow opening, ensuring they are centrally positioned and then screw Overflow Cover⑫ on to central spindle . Control Cable⑨b is not twisted before fully tightening Overflow Cover⑫ . In the event that the Control Cable is twisted or jammed, the pop-up mechanism will not operate.

打开(17295T-CP)排水包装，确保控制线 ⑨b 没有扭曲打结。
请将浴缸放置在木架或硅墙上保障排水配件在浴缸底下。

安装步骤：
1) 将橡胶密封圈⑤垫于去水滤网④处。
2) 从浴缸的上方将去水滤网④插入排水口。
3) 将橡皮密封圈⑥垫于去水本体⑨上并置于浴缸底部，排水口下端。
4) 用固定螺栓③固定滤网④和去水本体⑨， 注意在此时不要将螺丝旋得太紧。
5) 从浴缸的外面朝溢水口处涂一圈密封硅胶。再在溢水口内壁处涂上硅胶。(如图)
6) 将另一块橡皮密封圈⑭垫于溢水头⑨a上，然后放在浴缸溢水口的背面并确保它们置中放置。
用螺丝将溢水面板⑫固定到中心轴上。在拧紧溢水面板⑫前请确保控制线⑨b没有扭曲打结。控制线打结或扭曲会造成提拉式去水工作失灵。

E. 局部安装按摩浴缸的排水配件

按照厂家说明书，把排水配件部份安装在按摩浴缸上，安装排水管的溢水管和盖时，确保溢水盖的边缘充分密封，以防漏水。



7) Centralise Grating ④ with Waste Body ⑨ by lining up ribs of each directly in line and tighten Fixing Screw ③ with a coin or suitable screwdiver.
Do not overtighten - handtight plus 1/4 turn should be sufficient.

8) Adjust Plug ① by twisting Control Knob ⑩ to the 'up' position and then fix Plug height by use of Adjusting Screw ②.

9) Secure Flexible Pipe ⑬ by tightening Compression Nut ⑧ against Compression Seal ⑦.

10) Set drain pipe ⑯, put on nut drain pipe ⑰, and then tighten gasket ⑮.
Check if the pop-up mechanism is operating correctly. If it doesn't the Plug height still needs adjusting or Control Cable might be twisted or jammed. Proceed with bath installation only after you've ensured the drain is operating correctly.

7) 将滤网④和去水本体⑨置中排列并排成一线后用硬币或电钻来固定螺拴③。
不要过分拧紧-----用手上紧后再拧紧至合适松紧。

8) 旋转控制钮⑩来调节塞子①到放水的位置，然后使用调节螺丝②固定塞子的高度。

9) 旋紧在压缩密封圈⑦后的压缩螺母⑧来调节和固定软管⑬。

10) 安装排水管⑯，套上排水管螺帽⑰，并垫上密封垫片⑮旋紧。
检查使用提拉式排水正常工作。
如果塞子不能够提拉到工作高度的话，需要调节控制线看它是否扭曲打结。在您检查并确认浴缸排水工作正常后才进行浴缸的下步安装。

F. Protect Whirlpool Unit

Position a protective covering or similar material in the bottom of the the unit. Be careful not to scratch the surface of the product.

F. 保护按摩浴缸

在浴缸表面盖上抹布或类似材料。小心不要刮伤按摩浴缸表面。

INSTALL THE WHIRLPOOL

安装按摩浴缸

Whirlpool Set-In

If the subfloor is not level, some shimming of the bath will be necessary.

Set the whirlpool into installation. Make sure the unit is level, and is resting on all supporting feet. Insert the drain tailpiece into the trap. Apply a bead of silicone sealant under the rim of the whirlpool.

NOTICE: Do not hang the whirlpool by the rim.

放置按摩浴缸

若底层地板没有水平，必须用垫块将浴缸支平。

将按摩浴缸放入安装位置。确保浴缸水平位置，并且所有重量都均匀地承载在支脚上。将排水管尾端插入存水弯。在按摩浴缸边缘下方抹上一圈密封硅胶。

注意：不要靠边缘将按摩浴缸悬挂。



COMPLETE FINISH WALL 完成墙壁装修

Drop-In Models:

⚠ **CAUTION: Risk of product damage.** Do not support the weight of the bath by the rim.

无裙边浴缸类型：

⚠ 注意：当心损坏浴缸。不要靠浴缸边缘支撑浴缸的重量。

For sunken type installation, construct the ceramic or marble tiles. Seal the joints between the bath rim and the tiled wall with silicone sealant.

对嵌入式安装，在敷上瓷砖或大理石贴面后，再用硅胶密封浴缸边缘和贴面的连接处。



INSTALL PLUMBING 安装卫生管道

CAUTION: Risk of damage to bath bottom and subfloor, Ensure a watertight seal on the bath drain connections.

A. When the bath is securely positioned, connect the drain to the trap.
NOTE: An access panel will simplify future maintenance.
B. Install the faucet valving and spout tee. When drilling bathtub for faucet, ensure sufficient clearance to avoid brick support wall. Open the hot and cold water valves and check the supply connections for leaks.
C. Run water into the bath and check the drain connections for leaks.
D. Fill the whirlpool up to the overflow level and check overflow unit for leaks.

注意：避免损坏浴缸底部和底层地面。浴缸的所有排水接口都要确保做防渗密封。

A. 当浴缸固定到位后，将排水管与存水弯相接。

注意：为方便以后维修，一定要安装一个检修门。

B. 安装水龙头阀门及喷头三通。在浴缸上钻孔安装龙头时，请保证留有足够的间距，避免触及支撑框架。打开冷水及热水阀门，检查所有给水管接头是否渗漏。

C. 将浴缸注入水，检查排水配件接头是否有渗漏。

D. 注水至溢水口高度，检查溢水组件是否有渗漏。

E. Connect power supply (220V/50Hz, 10A) to motor. This should be a separato line, direct from the switchboard.
Connect power supply (220V/50Hz, 10A) to heater. This should be a separato line, direct from the switchboard.

The electrical connections must comply with local authority regulations and must be done by an authorized electriclan. Please refer to Spa Pump Installarion & Operation Instructions sheet.

F. Fill bathtub with water to approximately 40 mm above the jets and trial run pump for 10-15 minutes. Check all the fittings for leaks and test the control functions. Switch off the spa pump and leave the unit filled with water (pump is not running) for at least another two minutes. Check the pump and pipes union connections for leaks. Hand tighten union connections if required.

E. 将水泵连接到额定电压为220V/50Hz，额定电流为10A的供电线路上，这根电源线应该是单独的从开关箱上接出。
将加热器连接到额定电压为220V/50Hz，额定电流为10A的供电线路上，这根电源线应该是单独的从开关箱上接出。

电气连接必须由授权电工来完成，操作必须符合当地电气规范。请按照按摩水泵系统安装说明及操作手册来安装。

F. 将浴缸注入水，水位高过喷头大约40mm，试运行水泵10-15分钟。检查所有的部件是否有渗漏并测试控制系统。关闭按摩水泵并让浴缸注满水(水泵不运行)至少2分钟。检查水管连接处是否有渗漏。如有必要的话将各接头处再拧紧。

IMPORTANT: Your spa has been factory tested and approved. It is the responsability of the installer to test run the spa check all the fittings for leaks and test the control functions.
NON OBSERVANCE WILL INVALIDATE FACTORY WARRANTY.

重要信息：按摩浴缸已经工厂检测通过。安装人员有责任检查按摩浴缸的工作情况，检查所有安装有无渗漏。检查控制功能。疏忽导致的损坏，不能获得工厂的保修。

DRILLING AND CUTTING ACRYLIC 在压克力表面上钻孔和切割

DRILLING: Small holes can be drilled with a twist drill, but the cutting edge MUST be backed off with an oil stone (the sharp edge dulled). Large holes must be drilled with a hole saw. Maximum drill size-12mm. Drill speeds-6mm × 1800 RPM-12 mm × 900 RPM.

钻孔：可用一麻花钻头钻小孔，但切削刃必须用一块油石磨钝。大孔须用孔钻加工。麻花钻头的最大尺寸为12mm，速度为6mm ×1800转/分至12mm ×900转/分。

NOTE: Always drill from acrylic surface.

注意：钻孔要从压克力表面钻向浴缸背面。

CUTTING: If for any reason the acrylic requires cutting, use a fine tooth hacksaw and proceed with caution. Edges can be smoothed with a second-cut file and medium-fine sandpaper. If the surface of the acrylic should happen to be damaged, it can be restored by polishing with an abrasive cleaner. Deep scratches can be removed by rubbing with 600 grade wet & dry sandpaper then polishing.

切割：如果因故需要切割压克力，请用优质齿型钢锯仔细切割。边缘可用一旧锉刀及中等砂纸磨平。如果压克力表面受损，可用磨蚀性清洁剂抛光，将其恢复。深度刮伤可用600号水砂纸磨平，然后抛光。

CLEAN-UP AFTER INSTALLATION 完工清理

When cleaning up after installation, do not use abrasive cleansers as they may scratch and dull the surface. Use warm water and liquid, non-abrasive detergent to clean the surface.

在安装完成后进行清理时，请勿使用磨损性的清洁用具，以免擦伤浴缸表面，使其失去光泽。使用温水和非腐蚀性的液体清洁剂，清洗浴缸表面。

Stubborn stains, paint, or tar can be removed with mineral spirits. Do not use cleaners containing solvent. Plaster can be removed by scraping with wood edge. Do not use metal scrapers, wire brushes, or other metal tools. One of the powder type detergents may be used on a damp cloth to provide mild abrasive action to the residual plaster.

难以清除的污迹、油漆、或柏油，可用酒精擦净。请不要让含有溶剂的清洁剂。滞留水泥可用薄木刀刮掉。请不要使用金属刮刀，钢丝刷，或其它金属工具。对残留的水泥浆，可用湿布粘些洗衣粉，以提供轻微的研磨作用。

IMPORTANT CONSUMER INFORMATION 重要的用户资料

Consumer Responsibilities

用户的责任

Cleaning Acrylic Surfaces: Do not use abrasive cleansers on any acrylic surfaces, as they will scratch and dull the surface. Wipe out the bath after each use to prevent a build-up of soap and scum.

清洗压克力表面：请勿在压克力表面使用磨损性的清洁用具，以免擦伤浴缸表面，使其失去光泽。每次使用后，将浴缸擦干，以防止肥皂和污垢沉积。

If the acrylic surface becomes dull, an automotive type rubbing compound *may be used on the unit, followed by an application of paste wax.

若压克力表面失去光泽，先用汽车抛光剂*，然后再用粗腊打亮。

*We recommended:
Rubbing compound mequiars mirror glaze 28 metal polish (import product) or "green oil".

*我们推荐使用以下2种抛光剂：
① Mequiars 镜面光亮28金属上光剂。(进口)
② 抛光膏(绿油)。

LIMITED ONE-YEAR WARRANTY 一年有限担保

Plumbing Fixtures and Fittings Limited One-year Warranty

Kohler plumbing fixtures and fittings are warranted to be free of manufacturing defects.

This product is warranted for one year from date of purchase. Kohler China will be responsible for any problems caused by manufacturing defects provided with the invoice. Kohler China will, at its election, repair, replace or make appropriate adjustment where Kohler China inspection discloses any such defects occurring in normal usage within one year after purchase.

Implied warranties including that of merchantability and fitness for a particular purpose are expressly limited in duration to the duration of this warranty, Kohler China disclaims any liability for special, incidental or consequential damages. Damages to the product caused by misuse, abuse and installation that is not in accordance with the owner's manual are not covered by this warranty.

To obtain quick warranty service, please contact your dealer, or write to Kohler China. (Original sales receipt must be provided as the proof of purchase.)

Kohler China Investment Company Ltd.
Central Customer Service Center
19/F, Shanghai Square, 138 Huai Hai Road, Luwan District, Shanghai, PRC
Zip Code: 200021

This is our exclusive written warranty.

陶瓷及浴缸产品及配件担保——一年有限担保

科勒公司担保其陶瓷及浴缸产品及配件在制造工艺上无瑕疵。

本产品自购买之日起即获得本公司一年的质量保证。在质保期内，凭购货发票，科勒公司将免费承担由制造质量引起的任何问题。经核查后，科勒中国有限公司有权决定是修理、更换、还是作适当的调整。

这里所指的担保，包括产品，都已明确地限制在该担保期之内。科勒中国有限公司对其后出现的损坏不负有任何责任。担保也不包括外观损伤、使用不当以及未按说明书安装的损失。

为获得快捷的担保服务，请联系您的销售商；您也可写信给科勒中国有限公司(请出示销售发票原件作为购货凭证)：

科勒(中国)投资有限公司
中央客户服务中心
上海市卢湾区淮海中路138号
上海广场19楼
邮编：200021

这是我们全部的书面担保。